



When Buying From Deso, You Are Buying More Than Products, You Are Buying Quality And Service

## ELECTRIC WIRE ROPE HOIST(W TYPE)

- ✓ High Reliable Braking System
- ✓ Hoist Motor With Thermal Protector
- ✓ Widely Used In Factories, Mines, Harbours, Warehouse, Cargo Storage Areas And Shops
- ✓ Essential In Raising Working Efficiency And Improving Working Conditions.



Capacity(T)		1			2			3			5			10		
Lift Height(M)		6	9	12	6	9	12	6	9	12	6	9	12	6	9	12
Lift Speed(M/Min)		11			6			7.5			6.7			5		
Travelling Speed(M/Min)		21(25)			21(25)			21(25)			21(25)			21(25)		
Spec.Of Wire Rope	Rope Dia(mm)	8			12			14			14			15.5		
	Wire Dia(mm)	0.34			0.5			0.6			0.6			0.7		
	Construction	7*19-B			6*37-B			6*37-B			6*37-B			6*37+1-B		
I Beam		20a-45a			20a-45a			30a-63a			45a-63a			45a-63a		
Min. Radius of Rail(M)		1.5			1.8			2.0			3.0			Straight Line		
Lifting Motor	Model	IM6			2M7			3M6			5M5			10M		
	Power(KW)	3			3			5.5			7.5			11		
	Rotation	1380			1380			1380			1380			1380		
	Phase	3			3			3			3			3		
	Voltage(v)	380			380			380			380			380		
	Currency	6.44			6.44			11.8			15.6			22.3		
	Frequency	50HZ			50HZ			50HZ			50HZ			50HZ		
Travelling Motor	Model	1T5			2T5			3T5			5T5			5FT5		
	Power(KW)	0.4			0.4			0.4			0.75			0.75*2		
	Rotation	1380			1380			1380			1380			1380		
	Phase	3			3			3			3			3		
	Voltage(V)	380			380			380			380			380		
	Currency (A)	1.5			1.5			1.5			2.0			2.0		
	Frequency	50HZ			50HZ			50HZ			50HZ			50HZ		